

Printing date 09/15/2021

Revision date 09/15/2021

Page 1/11

### **1** Identification

- · Product identifier
- · Trade name: SM-102
- Article number: 33474
- Application of the substance / the mixture This product is for research use - Not for human or veterinary diagnostic or therapeutic use. It is the responsibility of the purchaser to determine suitability for other applications.
- Details of the supplier of the safety data sheet
   Manufacturer/Supplier: Cayman Chemical Co.
   1180 E. Ellsworth Rd. Ann Arbor, MI 48108 USA
- · Information department: Product safety department
- Emergency telephone number: During normal opening times: +1 (734) 971-3335 US/CANADA: 800-424-9300 Outside US/CANADA: 703-741-5970

### 2 Hazard(s) identification

Classificati	ion of the substance or mixture	
GI	HS02 Flame	
Flam. Liq. 2	2 H225 Highly flammable liquid and vapor.	
GI	HS06 Skull and crossbones	
	<ul><li>3 H301 Toxic if swallowed.</li><li>3 H331 Toxic if inhaled.</li></ul>	
GI	HS08 Health hazard	
Carc. 1A	H350 May cause cancer.	
		(Contd. on page

Printing date 09/15/2021

Revision date 09/15/2021

## Trade name: SM-102

(Contd. from page 1)

Label elements GHS label element The product is class Hazard pictograms	sified and labeled according to the Globally Harmonized System (GHS).
Label elements GHS label element The product is class Hazard pictograms	<b>ts</b> sified and labeled according to the Globally Harmonized System (GHS).
GHS label element The product is class Hazard pictograms	sified and labeled according to the Globally Harmonized System (GHS).
The product is class Hazard pictograms	sified and labeled according to the Globally Harmonized System (GHS).
Hazard pictograms	
Hazard pictograms	
GHS02 GHS06	GHS07 GHS08
Signal word Dange	er
	ng components of labeling:
ethanol	
Hazard statements	
	flammable liquid and vapor.
H301+H331 Toxic i	if swallowed or if inhaled.
H319 Causes	s serious eye irritation.
	ause cancer.
Precautionary stat	
	Obtain special instructions before use.
	Do not handle until all safety precautions have been read and understood.
	Keep away from heat/sparks/open flames/hot surfaces No smoking.
	Ground/bond container and receiving equipment.
	Use explosion-proof electrical/ventilating/lighting/equipment.
	Use only non-sparking tools.
	Take precautionary measures against static discharge.
	Avoid breathing dust/fume/gas/mist/vapors/spray
	Wash thoroughly after handling.
	Do not eat, drink or smoke when using this product.
P271 I	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
	If swallowed: Immediately call a poison center/doctor.
	Specific treatment (see on this label).
	Rinse mouth.
	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin wit
	water/shower.
	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses,
	present and easy to do. Continue rinsing.
	IF exposed or concerned: Get medical advice/attention.
	If eye irritation persists: Get medical advice/attention.
	In case of fire: Use CO2, powder or water spray to extinguish.
	Store in a well-ventilated place. Keep container tightly closed.
	Store in a well-ventilated place. Keep cool.
	Store locked up.
P501 I	Dispose of contents/container in accordance with local/regional/national/international
I	regulations.
	(Contd. on page 3

-US

Printing date 09/15/2021

Revision date 09/15/2021

(Contd. from page 2)

90.0%

10.0%

### Trade name: SM-102

Classification system:
 NFPA ratings (scale 0 - 4)

200 F

Health = 2 Fire = 0 Reactivity = 0

#### · HMIS-ratings (scale 0 - 4)

HEALTH\*2FIRE0FIRE0REACTIVITY0Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

### **3 Composition/information on ingredients**

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

### · Dangerous components:

CAS: 64-17-5 ethanol RTECS: KQ6300000

· Other ingredients

2089251-47-6 SM-102

### 4 First-aid measures

#### · Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

Remove breathing apparatus only after contaminated clothing have been completely removed. In case of irregular breathing or respiratory arrest provide artificial respiration.

• After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed May cause anemia, cough, CNS depression, drowsiness, headache, heart damage, lassitude (weakness, exhaustion), liver damage, narcosis, reproductive effects, teratogenic effects.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. on page 4)

Printing date 09/15/2021

Revision date 09/15/2021

Trade name: SM-102

(Contd. from page 3)

### **5 Fire-fighting measures**

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available. • Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

### 6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
   Environmental precautions:
- Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation. • **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.
- Protective Action Criteria for Chemicals

 · PAC-1:
 64-17-5
 ethanol
 1,800 ppm

 · PAC-2:
 64-17-5
 ethanol
 3300\* ppm

 · PAC-3:
 64-17-5
 ethanol
 15000\* ppm

### 7 Handling and storage

- · Handling:
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
   Protect against electrostatic charges.
   Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 5)

US

Printing date 09/15/2021

Revision date 09/15/2021

(Contd. from page 4)

Trade name: SM-102

· Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

#### · Control parameters

· Components with limit values that require monitoring at the workplace:

#### 64-17-5 ethanol

PEL Long-term value: 1900 mg/m<sup>3</sup>, 1000 ppm

- REL Long-term value: 1900 mg/m<sup>3</sup>, 1000 ppm
- TLV Short-term value: 1000 ppm
  - A3

· Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

### · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

US

Printing date 09/15/2021

Revision date 09/15/2021

(Contd. from page 5)

US

### Trade name: SM-102

• Eye protection:



Tightly sealed goggles

#### 9 Physical and chemical properties · Information on basic physical and chemical properties General Information · Appearance: Form: Liquid Color: According to product specification · Odor: Characteristic · Structural Formula C44H87NO5 · Molecular Weight 710.2 · Odor threshold: Not determined. · Formulation A solution in ethanol · pH-value: Not determined. · Change in condition Melting point/Melting range: Undetermined. 78 °C (172.4 °F) **Boiling point/Boiling range:** · Flash point: 13 °C (55.4 °F) · Flammability (solid, gaseous): Not applicable. · Ignition temperature: 982 °C (1,799.6 °F) · Decomposition temperature: Not determined. · Auto igniting: Product is not selfigniting. • Danger of explosion: Product is not explosive. However, formation of explosive air/ vapor mixtures are possible. · Explosion limits: 3.5 Vol % Lower: 15 Vol % Upper: · Vapor pressure at 20 °C (68 °F): 59 hPa (44.3 mm Hg) Density at 20 °C (68 °F): 1.47988 g/cm<sup>3</sup> (12.3496 lbs/gal) · Bulk density: 1,480 kg/m<sup>3</sup> · Relative density Not determined. · Vapor density Not determined. · Evaporation rate Not determined. · Solubility in / Miscibility with Water: Fully miscible. · Partition coefficient (n-octanol/water): Not determined. · Viscosity: Dynamic at 20 °C (68 °F): 0.56 mPas (Contd. on page 7)

Printing date 09/15/2021

Revision date 09/15/2021

Trade name: SM-102

	(Contd. from page
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	90.0 %
VOC content:	90.00 %
	1,331.9 g/l / 11.12 lb/gal
Solids content:	0.0 %
Other information	No further relevant information available.

## **10 Stability and reactivity**

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- Hazardous decomposition products: No dangerous decomposition products known.

## **11 Toxicological information**

- · Information on toxicological effects
- · Acute toxicity:

64-17-5 ethanol		
Oral	TDLO	1.14 ml/kg (man)
	LD50	7,060 mg/kg (rat)
	TDLO	650 (man)
Dermal	LD50	40,000 mg/kg (rat)
Inhalative	LC50/4 h	5,900 mg/m³ (rat)
	LC50	20,000 mg/m³/10h (rat)
	TCLO	1,800 mg/m³/30m (hmn)
	LCLO	29,300 mg/m³/7h (mouse)
	TCLO	1,800 (hmn)
	LC50	10 h - 20,000 mg/m³ (rat)
	LD50 Inhalation TCLO	1,800 mg/m³/30m (hmn)
	LC50/4 h	20,000 mg/l (rat)
Irritation of skin	Irritation	20 mg/24h (rabbit)
	TDLO	1,800 mg/kg (wmn)
Irritation of eyes	Irritation	500 mg/24h (rabbit)
	Intraperitoneal LD50	280 mg/kg (rat)
	Data	500 mg/24h (rabbit)

• on the skin: No irritant effect.

· on the eye: Irritating effect.

Printing date 09/15/2021

Revision date 09/15/2021

(Contd. from page 7)

1

#### Trade name: SM-102

<ul> <li>Sensitization: No sensitizing effects known.</li> </ul>	
• Additional toxicological information:	

The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic

Irritant

### · Carcinogenic categories

· IARC (International Agency for Research on Cancer)

64-17-5 ethanol

## • NTP (National Toxicology Program)

None of the ingredients is listed.

### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### **12 Ecological information**

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

### **13 Disposal considerations**

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

## 14 Transport information

- · UN-Number
- · DOT, IMDG, IATA

UN1170

(Contd. on page 9)

US

Printing date 09/15/2021

Revision date 09/15/2021

Trade name: SM-102

	(Contd. from page
UN proper shipping name	
DOT	Ethanol solutions
·IMDG	ETHANOL SOLUTION (ETHYL ALCOHO
14-74	SOLUTION)
ΙΑΤΑ	Ethanol solution
· Transport hazard class(es)	
DOT	
RAMARE DOD	
Class	3 Flammable liquids
Label	3
· Class	3 Flammable liquids
Label	3
Packing group DOT, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code):	
EMS Number:	F-E,S-D
Stowage Category	A
· Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
· · · · · · ·	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
·IATA	
	(Contd. on page
	(Conta: of page

Printing date 09/15/2021

Revision date 09/15/2021

Trade name: SM-102

	(Contd. from page 9)
· Remarks:	When sold in quantities of less than or equal to 1 mL, or 1 g, with an Excepted Quantity Code of E1, E2, E4, or E5, this item meets the De Minimis Quantities exemption, per IATA 2.6.10. Therefore packaging does not have to be labeled as Dangerous Goods/Excepted Quantity.
· UN "Model Regulation":	UN 1170 ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION), 3, II

Safety, health and environmental regulations/legislation specific for the s Sara	ubstance or mixture
Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
Section 313 (Specific toxic chemical listings):	
None of the ingredients is listed.	
TSCA (Toxic Substances Control Act):	
64-17-5 ethanol	ACTIV
Hazardous Air Pollutants	
None of the ingredients is listed.	
Proposition 65	
Chemicals known to cause cancer:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
64-17-5 ethanol	
Carcinogenic categories	
EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
TLV (Threshold Limit Value)	
64-17-5 ethanol	A
NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	
National regulations:	
• Information about limitation of use: Workers are not allowed to be exposed to the hazardous carcinogenic ma preparation. Exceptions can be made by the authorities in certain cases.	aterials contained in t

preparation. Exceptions can be made by the authorities in certain cases. • **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

us

Printing date 09/15/2021

Revision date 09/15/2021

#### Trade name: SM-102

(Contd. from page 10)

### **16 Other information**

All chemicals may pose unknown hazards and should be used with caution. This SDS applies only to the material as packaged. If this product is combined with other materials, deteriorates, or becomes contaminated, it may pose hazards not mentioned in this SDS. Cayman Chemical Company assumes no responsibility for incidental or consequential damages, including lost profits, arising from the use of these data. It shall be the user's responsibility to develop proper methods of handling and personal protection based on the actual conditions of use. While this SDS is based on technical data judged to be reliable, Cayman Chemical Company assumes no responsibility for the completeness or accuracy of the information contained herein.

· Department issuing SDS: Environment protection department.

- · Contact: -
- · Date of preparation / last revision 09/15/2021 / -
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flam. Liq. 2: Flammable liquids - Category 2 Acute Tox. 3: Acute toxicity - Category 3 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Carc. 1A: Carcinogenicity - Category 1A \* \* Data compared to the previous version altered.